



FITMENT GUIDE

*Rod widths based on factory wraps

The fitment guide is designed to help you select the correct clamp for your rod and reel setup. For your convenience, we have provided examples of rods and a scaled ruler. To ensure an accurate fit, it is always best to measure your rod where you intend to mount your reel with a set of calipers.



COMPATIBLE REELS

Shimano: Torium 14-50, Trinidad A 12-50, Trinidad 12-50, Calcutta 400-700, Tranx 400-500, Talica 8-20, Tyronos 20-30, Speedmaster 12-16
Daiwa: Saltiga 15-50, Saltist 15-50, Seagate 20-50, Lexa 400
Okuma: Komodo 463, Komodo 471
Penn: Torque 15-40, Fathom 15-50, Squall 15-40, Warfare 15-30
Avet: JX,HX,LX
Accurate: Valiant 400-600, Tern 400-600, Boss 400-600, Dauntless 400-600, Fury 400-600



Min Rod Diameter 1.125 (1 1/8) 28.5 MM Max Diameter 1.5 (1 1/2) 38MM


ROD EXAMPLES

Seeker: WTS 7X, All Uluas, 540, 6480, 6470, D8, 6490
CalStar: 100J, 90J, 800H, 690J, 6480
Phenix: HAX1009, HAX1008, HAX909, PSW809, PSW909



COMPATIBLE REELS

Shimano: Tranx 300-500, Trinidad 10-30, 16NA, Torium 14-30
Daiwa: Saltiga 10-30, Saltist 15-40, Lexa 300-400 * Does not fit Lexa 300 Models 2020 and newer
Okuma: Komodo 364, Komodo 463-471
Avet: SXJ * Does not fit Raptor model
Penn: Fathom™ 400 Baitcaster, Fathom™ 8XN, 12, 15, 25, 30, 25N, Squall™ 12, 15, 30, 40, 25N, Torque™ 15, 30, 25N
Accurate: Valiant 400-600, Tern 400-600, Boss 400-600, Dauntless 400-600, Fury 400-600, Fits 400-500 series narrow reels, Does not fit 300 series Accurate reels



Min Rod Diameter .625 (5/8) 15.875MM Max Rod Diameter 1.125 (1 1/8) 28.5MM

ROD EXAMPLES

Seeker: 270H, 270, 196-8
CalStar: 270, 800M, 800L, 196
Phenix: SMX Series, PSX Series
United Composites: All Deckhand Rods
Shimano: All Deckhand Rods



Measure at point of rod where clamp will be mounted